

# JS12-14





## General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Excellent deep cycle discharge capability
- Strong high and low temperature performance
- Precision sealing technology



Dimension: 151(L)×98(W)×95(H)×100(TH) Unit: mm



# JS Series lead-acid battery

## Applications

- UPS/EPS
- Power systems
- Telecommunications system
- Emergency lighting, Auto control system
- Solar/wind generating storage cyclic
- Other general purpose

## Specification

|                        |  |
|------------------------|--|
| Nominal Voltage        | 12V  |
| Nominal Capacity       | 14.0Ah   |
| Design life            | 5 years  |
| Terminal               | F1/F2/F3   |
| Approx. Weight         | Approx 3.70kg (8.16lbs)                              |
| Container Material     | ABS  |
| Rated Capacity         | 14.0Ah → 20Hour Rate (0.70A to 10.5V)                |
|                        | 11.04Ah → 3Hour Rate (3.68A to 10.2V)                |
|                        | 9.24Ah → 1Hour Rate (9.24A to 9.60V)                 |
| Internal resistance    | Full charged at 25°C: 18.0 mΩ                        |
| Max. Discharge Current | 210A(5S)   |
| Operating Temperature  | Discharge: -20 ~50°C (-4 ~ 122°F)                    |
|                        | Charge: -20 ~50°C (-4 ~ 122°F)                       |
|                        | Storage: -20 ~50°C (-4 ~ 122°F)                      |
| Charge current:        | Max. 3.50A ; Recom. 1.40A                            |
| Charge Method (25°C)   | Float Charge: 13.5-13.8V, recom. 13.8V (-18mV/°C)    |
|                        | Equalize charge: 13.8-14.1V, recom. 14.1V (-24mV/°C) |
|                        | Cycle charge: 14.4-15.0V, recom. 14.7V (-30mV/°C)    |
| Self discharge         | 3% of capacity declined per month at 25°C            |

## Constant Current Discharge Characteristics Unit: A (25°C, 77°F)


| FV/Time | 5min | 10min | 15min | 30min | 45min | 1h   | 1.5h | 2h   | 3h   | 4h   | 5h   | 6h   | 8h   | 10h  | 20h   |
|---------|------|-------|-------|-------|-------|------|------|------|------|------|------|------|------|------|-------|
| 1.60V   | 55.4 | 36.3  | 27.0  | 17.7  | 11.3  | 9.24 | 5.65 | 5.29 | 3.86 | 3.09 | 2.63 | 2.00 | 1.74 | 1.39 | 0.742 |
| 1.65V   | 55.0 | 34.7  | 24.8  | 16.8  | 10.7  | 8.68 | 5.57 | 5.08 | 3.75 | 3.00 | 2.58 | 1.98 | 1.71 | 1.37 | 0.728 |
| 1.70V   | 45.1 | 32.6  | 23.1  | 16.3  | 10.3  | 8.40 | 5.45 | 4.98 | 3.68 | 2.84 | 2.55 | 1.93 | 1.68 | 1.34 | 0.714 |
| 1.75V   | 41.9 | 31.1  | 21.6  | 15.9  | 9.95  | 8.11 | 5.37 | 4.86 | 3.63 | 2.80 | 2.44 | 1.90 | 1.64 | 1.32 | 0.700 |
| 1.80V   | 38.5 | 29.3  | 20.0  | 15.4  | 9.60  | 7.83 | 5.25 | 4.73 | 3.43 | 2.74 | 2.34 | 1.86 | 1.60 | 1.29 | 0.672 |
| 1.85V   | 34.4 | 27.1  | 17.8  | 14.1  | 8.90  | 7.25 | 5.09 | 4.50 | 3.23 | 2.66 | 2.23 | 1.80 | 1.53 | 1.25 | 0.661 |

## Constant Power Discharge Characteristics Unit: W/cell(25°C, 77°F)


| FV/Time | 5min | 10min | 15min | 30min | 45min | 1h   | 1.5h | 2h   | 3h   | 4h   | 5h   | 6h   | 8h   | 10h  | 20h  |
|---------|------|-------|-------|-------|-------|------|------|------|------|------|------|------|------|------|------|
| 1.60V   | 104  | 65.3  | 49.5  | 29.9  | 20.3  | 16.9 | 11.4 | 9.92 | 7.30 | 5.86 | 4.97 | 3.95 | 3.28 | 2.69 | 1.47 |
| 1.65V   | 95.9 | 61.8  | 46.4  | 29.7  | 19.1  | 15.9 | 11.1 | 9.54 | 7.09 | 5.67 | 4.88 | 3.86 | 3.23 | 2.63 | 1.43 |
| 1.70V   | 87.7 | 60.0  | 44.3  | 29.6  | 18.5  | 15.4 | 11.0 | 9.36 | 6.98 | 5.39 | 4.74 | 3.83 | 3.19 | 2.61 | 1.42 |
| 1.75V   | 79.6 | 58.1  | 42.7  | 29.3  | 18.0  | 15.0 | 10.8 | 9.15 | 6.88 | 5.32 | 4.64 | 3.74 | 3.06 | 2.55 | 1.39 |
| 1.80V   | 71.4 | 56.2  | 40.8  | 29.1  | 17.8  | 14.8 | 10.6 | 9.08 | 6.70 | 5.27 | 4.53 | 3.67 | 2.96 | 2.50 | 1.38 |
| 1.85V   | 63.7 | 52.5  | 36.5  | 26.6  | 16.6  | 13.8 | 10.4 | 8.68 | 6.38 | 5.19 | 4.32 | 3.61 | 2.83 | 2.46 | 1.37 |

**JS12-14**


**Discharge characteristic**




**Charging characteristic**




**The effect of temperature on capacity**




**The effect of discharge depth on cycle life**



**Curves of self-discharge**



**The effect of temperature on float life**



[www.kijo.com.cn](http://www.kijo.com.cn)    [info@kijo.com.cn](mailto:info@kijo.com.cn)

**Jiangxi Jingjiu Power Science&Technology Co. Ltd.**  
Add: 1388 Fushan No.1 Street, Xiaolan Economic Development Zone, Nanchang City, Jiangxi Province, China.

+86-791-85982779    +86-791-85989842

**Jiangxi Jingjiu Power ( Jiujiang ) Co. Ltd.**  
Add: Xiwang Rd, Aicheng Industrial Park, Yongxiu Country, jiujiang City, Jiangxi Province, China.

