



JS Series lead-acid battery JS6-12


General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Excellent deep cycle discharge capability
- Strong high and low temperature performance
- Precision sealing technology



Dimension:151(L)×51(W) ×94(H)×100(TH)/(±2.0)

Unit: mm



Specification

Nominal Voltage	6V
Nominal Capacity	12.0Ah@20hour-rate to 1.75V per cell @25°C
Design life	5 years
Terminal	F1/F2
Approx. Weight	Approx1.75kg±3% (3.86lbs±3%)
Container Material	ABS(UL94-HB, UL94-V0 Optional)
short-circuit current	666A
Internal resistance(Full charged at 25°C:)	9.0 mΩ
Self discharge	3% of capacity declined per month at 25°C

Operating Temperature

Discharge:	-20 ~50°C(-4~ 122°F)
Charge :	-20 ~50°C(-4~ 122°F)
Storage:	-20 ~50°C(-4~ 122°F)

Charge Method(25 °C)

Charge current:	Max. 3.5A;Recom.1.4A
Float charge:6.75-6.90V	recom.6.75V(-9mV/ °C)
Equalize charge:6.90-7.05V	recom.7.05V(-12mV/ °C)
Cycle charge:7.20-7.50V	recom.7.35V(-15mV/ °C)

Standards

Executive standard: IEC 61056-2,
GB/T 19639.1-2014

Applications

- UPS/EPS
- Power systems
- Telecommunications system
- Emergency lighting, Auto control system
- Solar/wind generating storage cyclic
- Other general purpose

Rated Capacity

20Hour Rate (0.600A to 5.25V)	12.0Ah
3Hour Rate (3.648A to 5.10V)	10.944Ah
1Hour Rate (8.653A to 4.80V)	8.653Ah


Attain Certificate




Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.




JS Series lead-acid battery JS6-12




Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of temperature on float life



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	5min	10min	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	51.91	36.10	26.33	15.55	11.02	8.653	6.195	5.187	3.908	3.086	2.593	2.219	1.679	1.376	0.626
1.65V	49.02	34.03	24.91	14.77	10.51	8.249	5.982	5.021	3.787	3.002	2.525	2.172	1.660	1.359	0.614
1.70V	44.68	31.57	23.33	14.27	10.15	7.954	5.788	4.856	3.648	2.920	2.460	2.101	1.634	1.338	0.606
1.75V	40.44	29.54	22.50	13.64	9.663	7.663	5.548	4.686	3.575	2.846	2.398	2.038	1.612	1.323	0.600
1.80V	35.51	26.77	20.77	13.03	9.301	7.370	5.390	4.556	3.464	2.764	2.336	1.966	1.584	1.308	0.590
1.85V	28.18	21.75	17.24	11.23	8.115	6.610	4.981	4.140	3.202	2.569	2.178	1.870	1.487	1.227	0.549

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	5min	10min	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	86.89	59.58	45.54	28.24	20.85	16.28	11.84	9.830	7.394	5.924	4.998	4.298	3.278	2.704	1.429
1.65V	82.21	57.72	44.19	27.40	19.81	15.85	11.65	9.563	7.222	5.785	4.886	4.153	3.248	2.675	1.408
1.70V	76.63	54.97	42.00	26.45	18.97	15.13	11.27	9.299	7.027	5.649	4.775	4.049	3.205	2.638	1.394
1.75V	70.89	52.81	41.09	25.54	18.61	14.80	10.85	9.016	6.916	5.525	4.671	3.959	3.167	2.607	1.384
1.80V	63.57	48.63	38.48	24.66	17.97	14.18	10.58	8.809	6.728	5.386	4.567	3.874	3.120	2.569	1.366
1.85V	51.52	40.45	32.39	21.45	15.96	12.90	9.739	8.049	6.248	5.025	4.273	3.694	2.936	2.429	1.287