



Electric vehicle battery expert 6-EVF-32.3L




General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Strong high and low temperature performance
- Low self-discharge rate



Dimension:267(L)×77(W) ×165(H)×170(TH)/(±2)

Unit: mm



Specification	
Nominal Voltage	12V
Nominal Capacity	32.3Ah@3Hour-rate to 1.75V per cell @25℃
Design life	5 years
Terminal	M5
Approx. Weight	Approx. 9.00kg±3% (19.84lbs±3%)
Container Material	ABS
Self discharge	3% of capacity declined per month at 25℃
Rated Capacity	
20Hour Rate (2.0A to 10.5V)	40.0Ah
5Hour Rate (7.0A to 10.5V)	35.0Ah
3Hour Rate (10.8A to 10.5V)	32.3Ah
Operating Temperature	
Discharge:	-20 ~50℃(-4~ 122°F)
Charge :	-20 ~50℃(-4~ 122°F)
Storage:	-20 ~50℃(-4~ 122°F)
Charge Method(25 °C)	
Max charge current	4.8A
Float Use:	13.7-13.9V@25
Cycle Use :	14.7-14.9V,@25

Standards

Executive standard :GB/T32620-2016

Applications

- Electric vehicle
- Electric wheelchair
- Electric scooter
- Electric play car for children
- Garbage truck
- Patrol car


Attain Certificate




Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.




Electric vehicle battery expert 6 - EVF-32.3L



Discharge characteristic




Charging characteristic




First stage: constant current 7.0-7.5A charge to voltage 14.8V;
Second stage: constant voltage 14.8±0.05V charge to current decrease to 800-850mA;
Third stage: trickle charge, voltage: 13.8±0.1V.

The effect of temperature on capacity



The effect of discharge depth on cycle life



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	48.2	28.3	15.4	11.2	7.21	4.4	3.71	2.03
1.65V	47.3	28.1	15.4	11.1	7.17	4.36	3.67	2.02
1.70V	46.4	27.9	15.2	10.9	7.08	4.32	3.64	2.01
1.75V	46	27.5	15	10.8	7.00	4.28	3.6	2
1.80V	44	26.8	14.7	10.8	6.83	4.28	3.56	1.99
1.85V	40.2	24.8	14	10.1	6.49	4.08	3.46	1.95

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	87.2	53.7	29.2	21.3	13.5	8.55	7.13	4.02
1.65V	86.3	53.2	29.1	21.1	13.4	8.48	7.05	4
1.70V	86.3	52.8	29	20.9	13.3	8.44	6.97	3.98
1.75V	85.8	52.3	28.8	20.8	13.3	8.4	6.93	3.96
1.80V	83.5	51.8	28.7	20.8	13.1	8.32	6.85	3.94
1.85V	76.5	48.1	27.4	19.7	12.5	8.04	6.73	3.9