





General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Strong high and low temperature performance
- Low self-discharge rate



Dimension:182(L)×77(W×170(H)×170(TH)

Unit: mm



Specification

Nominal Voltage	12V
Nominal Capacity	24Ah@2Hour-rate to 1.75V per cell@25℃
Design life	5 years
Terminal	M5
Approx. Weight	Approx. 7.0kg±3% (15.4lbs±3%)
Container Material	ABS
Self discharge	3% of capacity declined per month at 25℃

Rated Capacity

20Hour Rate (1.425A to 10.5V)	28.5Ah
5Hour Rate (5.0A to 10.5V)	25.0Ah
2Hour Rate (12.0A to 10.5V)	24.0Ah

Operating Temperature

Discharge:	-20 ~50℃(-4~ 122°F)
Charge :	-20 ~50℃(-4~ 122°F)
Storage:	-20 ~50℃(-4~ 122°F)

Charge Method(25 °C)

Max charge current	3.60A
Float Use:	13.7-13.9V@25
Cycle Use :	14.7-14.9V,@25

Standards

Executive standard :T/ZJXDC 001-2021

Applications

- Electric vehicle
- Electric wheelchair
- Electric scooter
- Electric play car for children
- Garbage truck
- Patrol car

Attain Certificate



Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.




Electric vehicle battery expert


6-DZF-24




Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of discharge depth on cycle life



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	35.9	19.8	12.40	8.40	5.45	3.11	2.63	1.456
1.65V	35.2	19.6	12.30	8.33	5.30	3.09	2.60	1.445
1.70V	34.5	19.5	12.20	8.20	5.15	3.06	2.58	1.438
1.75V	34.2	19.2	12.00	8.10	5.00	3.03	2.55	1.425
1.80V	32.7	18.7	11.80	8.07	4.78	3.03	2.52	1.400
1.85V	29.9	17.3	11.20	7.60	4.54	2.89	2.45	1.381

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	66.4	37.6	23.81	16.13	10.46	5.97	5.05	2.80
1.65V	65.1	37.2	23.62	15.99	10.18	5.93	4.99	2.77
1.70V	63.8	37.1	23.42	15.74	9.89	5.88	4.95	2.76
1.75V	63.3	36.5	23.04	15.55	9.60	5.82	4.90	2.74
1.80V	60.5	35.5	22.66	15.49	9.18	5.82	4.84	2.69
1.85V	55.3	32.9	21.50	14.59	8.72	5.55	4.70	2.65