



JH Series High-Rate Battery JH12-390W


General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Excellent deep cycle discharge capability
- Strong high and low temperature performance
- Precision sealing technology
- Long life



Dimension:307(L) ×168(W) ×211(H) ×214(TH)

Unit: mm



Specification

Nominal Voltage	12V
Nominal Capacity	3 90W@ 1 5 min- rate to 1 . 6 7V percell@ 2 5 °C
Design life	10 years
Terminal	M8
Approx. Weight	Approx31.0kg±3%(68.3 ±3%lbs)
Container Material	ABS(UL94-HB, UL94-V0 Optional)
short-circuit current	2666A
Internal resistance(Full charged at 25°C:)	4.5 mΩ
Self discharge	3% of capacity declined per month at 25°C

Operating Temperature

Discharge:	-20 ~50°C(-4~ 122°F)
Charge :	-20 ~50°C(-4~ 122°F)
Storage:	-20 ~50°C(-4~ 122°F)

Charge Method (2 5 ° C)

Charge current:	Max. 23.75A;Recom.9.5A
Float charge:13.5-13.8V	recom.13.8V(-18mV/ °C)
Equalize charge:13.8-14.1V	recom.14.1V(-24mV/ °C)
Cycle charge:14.4-15.0V	recom.14.7V(-30mV/ °C)

Standards

Executive standard: IEC 60896-21/22,
GB/T 19638.1-2014、YD/T 3427-2018

Applications

- UPS/EPS
- Power systems
- Telecommunications system
- Emergency lighting、Auto control system
- Solar/wind generating storage cyclic
- Other general purpose

Rated Capacity

10Hour Rate (9.50A to 10.8V)	95.0Ah
3Hour Rate (26.2A to 10.2V)	78.6Ah
1Hour Rate (66.0A to 9.6V)	66.0Ah

Attain Certificate




Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.




JH Series High-Rate Battery JH12-390W


Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of discharge depth on cycle life



Constant Current Discharge Characteristics Unit:A (25°C,77°F)

FV/Time	5min	10min	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	292.1	247.8	202.3	117.8	83.8	66.0	47.4	37.4	26.9	21.3	17.7	15.1	11.9	10.1	5.31
1.67V	262.6	229.0	186.8	115.2	82.2	65.3	46.8	36.7	26.5	20.8	17.4	14.9	11.8	9.96	5.21
1.70V	251.9	215.7	180.4	112.4	81.3	63.9	46.6	36.4	26.2	20.5	17.2	14.7	11.6	9.89	5.16
1.75V	232.6	202.2	170.6	107.7	77.7	61.1	44.6	35.2	25.4	20.0	16.8	14.5	11.4	9.65	5.10
1.80V	213.0	191.7	161.3	103.1	74.8	59.2	42.9	33.9	24.6	19.4	16.3	14.0	11.2	9.50	5.05
1.85V	189.1	162.4	138.8	91.2	66.0	53.1	39.1	31.0	22.7	18.0	15.2	13.1	10.6	9.07	4.81

Constant Power Discharge Characteristics Unit: W/cell (25°C,77°F)

FV/Time	5min	10min	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	575.8	483.3	408.7	234.3	169.6	135.7	98.0	77.6	56.2	44.7	37.4	32.0	25.5	21.8	11.4
1.67V	531.5	454.7	390.0	232.6	168.4	135.6	97.6	76.6	55.7	44.1	36.9	31.6	25.3	21.5	11.3
1.70V	505.1	436.6	377.2	228.2	167.3	133.1	97.4	76.4	55.3	43.4	36.5	31.4	24.9	21.3	11.2
1.75V	465.3	411.7	361.5	220.7	161.2	128.0	93.8	74.0	53.8	42.5	35.7	31.0	24.5	20.8	11.0
1.80V	431.6	387.3	344.7	213.4	156.4	124.8	90.8	71.7	52.4	41.3	34.9	30.0	24.2	20.5	10.9
1.85V	376.5	332.5	300.3	190.9	139.1	112.6	83.2	66.1	48.6	38.6	32.7	28.3	22.8	19.6	10.4