



JH Series High-Rate Battery JH12-530W


General Features

- ▶High corrosion resistant performance: Pb-Ca multi-alloy grid
- ▶High energy density and power density
- ▶Optimized capability of instant high-current discharging
- ▶Excellent charge acceptance ability
- ▶Excellent deep cycle discharge capability
- ▶Strong high and low temperature performance
- ▶Precision sealing technology
- ▶Long life



Dimension:336(L) × 172(W) × 279(H) × 279(TH)/(±2mm)

Unit: mm



Specification

Nominal Voltage	12V
Nominal Capacity	530W@ 1.5 min- rate to 1.67V percell@ 25°C)
Design life	10 years
Terminal	M8
Approx. Weight	Approx.44.0 ±3%kg (97.0 ±3%lbs)
Container Material	ABS(UL94-HB, UL94-V0 Optional)
short-circuit current	3157A
Internal resistance(Full charged at 25°C:)	3.8 mΩ
Self discharge	3% of capacity declined per month at 25°C

Operating Temperature

Discharge:	-20 ~50°C(-4~ 122°F)
Charge :	-20 ~50°C(-4~ 122°F)
Storage:	-20 ~50°C(-4~ 122°F)

Charge Method(25 °C)

Charge current:	Max. 36.25A;Recom.14.5A
Float charge:13.5-13.8V	recom.13.8V(-18mV/ °C)
Equalize charge:13.8-14.1V	recom.14.1V(-24mV/ °C)
Cycle charge:14.4-15.0V	recom.14.7V(-30mV/ °C)

Standards

Executive standard: IEC 60896-21/22,
GB/T 19638.1-2014, YD/T 2343-2011

Applications

- ▶UPS/EPS
- ▶Power systems
- ▶Telecommunications system
- ▶Emergency lighting, Auto control system
- ▶Solar/wind generating storage cyclic
- ▶Other general purpose

Rated Capacity

10Hour Rate (14.5A to 10.8V)	145.0Ah
3Hour Rate (41A to 10.2V)	123.0Ah
1Hour Rate (92.7A to 9.6V)	92.7Ah

Attain Certificate




Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.




JH Series High-Rate Battery JH12-530W


Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of discharge depth on cycle life



Constant Current Discharge Characteristics Unit:A (25°C,77°F)

FV/Time	5min	10min	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	454.9	362.1	298.0	171.8	122.1	92.7	72.2	60.0	42.1	34.1	28.4	24.3	18.6	15.5	8.52
1.67V	403.2	334.7	277.9	168.0	119.8	88.6	71.3	58.8	41.4	33.4	27.9	23.8	18.4	15.2	8.36
1.70V	386.8	315.2	268.3	163.9	118.5	86.8	71.0	58.4	41.0	32.9	27.6	23.6	18.0	15.1	8.28
1.75V	357.1	295.4	253.8	157.0	113.3	85.9	68.0	56.4	39.7	32.0	26.9	23.2	17.7	14.7	8.18
1.80V	327.0	275.8	240.0	150.2	109.1	83.3	65.4	54.4	38.5	31.1	26.2	22.4	17.5	14.5	8.09
1.85V	280.7	233.6	206.5	133.0	96.3	74.7	59.6	49.8	35.6	28.9	24.4	21.1	16.4	13.8	7.71

Constant Power Discharge Characteristics Unit: W/cell (25°C,77°F)

FV/Time	5min	10min	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	752.5	655.9	555.4	312.0	225.9	174.3	139.3	113.7	80.3	65.4	54.8	46.9	36.3	30.4	16.8
1.67V	667.2	617.2	530.0	309.8	224.2	168.0	138.6	112.3	79.6	64.5	54.1	46.4	36.0	29.9	16.5
1.70V	660.1	592.6	512.6	303.9	222.8	165.0	138.5	111.9	78.9	63.6	53.5	45.9	35.3	29.8	16.3
1.75V	611.7	558.8	491.3	294.0	214.7	164.4	133.4	108.5	76.9	62.2	52.4	45.4	34.9	29.0	16.2
1.80V	564.1	525.7	468.4	284.2	208.3	160.3	129.0	105.1	74.8	60.6	51.2	44.0	34.4	28.6	16.0
1.85V	492.1	453.6	408.2	254.2	185.3	144.7	118.3	96.8	69.4	56.5	47.9	41.5	32.4	27.4	15.3