



JM Series lead-acid battery JM12-100(C)





General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Excellent deep cycle discharge capability
- Strong high and low temperature performance
- Precision sealing technology
- Long life



Dimension:330(L)×171(W) ×216(H)×219(TH)/(±3)

Unit: mm



Terminal Dimensions

Specification	
Nominal Voltage	12V
Nominal Capacity	100Ah@10hour-rate to 1.80V per cell @25°C
Design life	10 years
Terminal	M8
Approx. Weight	Approx30.8kg ±3%(67.9±3%lbs)
Container Material	ABS(UL94-HB, UL94-V0 Optional)
short-circuit current	2307A
Internal resistance(Full charged at 25. C:)	5.2 mΩ
Self discharge	3% of capacity declined per month at 25. C
Operating Temperature	
Discharge:	-20 ~50°C(-4~ 122°F)
Charge :	-20 ~50°C(-4~ 122°F)
Storage:	-20 ~50°C(-4~ 122°F)
Charge Method(25 °C)	
Charge current:	Max. 25A;Recom.10A
Float charge:13.5-13.8V	recom.13.8V(-18mV/ °C)
Equalize charge:13.8-14.1V	recom.14.1V(-24mV/ °C)
Cycle charge:14.4-15.0V	recom.14.7V(-30mV/ °C)

Standards

Executive standard: IEC 60896-21/22,
GB/T 19638.1-2014

Applications

- UPS/EPS
- Power systems
- Telecommunications system
- Emergency lighting、Auto control system
- Solar/wind generating storage cyclic
- Other general purpose

Rated Capacity

10Hour Rate (10.0A to 10.8V)	100Ah
3Hour Rate (26.6A to 10.2V)	79.8Ah
1Hour Rate (63.2A to 9.6V)	63.2Ah

Attain Certificate




Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.




JM Series lead-acid battery JM12-100(C)


Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of temperature on float life



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	187.3	110.6	80.6	63.2	47.0	37.5	28.2	22.7	19.3	16.4	12.7	10.5	5.52
1.65V	179.9	106.2	77.3	60.8	45.6	36.7	27.3	22.0	18.8	16.2	12.5	10.4	5.43
1.70V	168.5	101.5	73.9	58.2	43.8	35.1	26.6	21.5	18.3	15.9	12.3	10.3	5.38
1.75V	156.8	96.0	70.7	56.4	42.0	33.9	25.8	21.0	17.9	15.5	12.2	10.1	5.35
1.80V	147.7	93.4	68.1	54.0	40.0	32.8	25.5	20.4	17.4	15.0	12.0	10.0	5.30
1.85V	122.6	79.1	59.5	47.4	36.2	29.1	22.4	18.5	15.9	13.7	11.2	9.22	5.08

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	329.0	200.9	146.6	115.8	87.0	69.0	53.2	42.6	36.4	31.6	24.8	20.7	10.9
1.65V	319.2	194.9	141.9	112.5	84.8	67.8	52.4	41.6	35.6	31.3	24.5	20.5	10.7
1.70V	303.4	188.1	140.2	109.6	83.6	65.6	50.2	40.6	34.8	30.6	24.2	20.2	10.6
1.75V	286.5	181.7	134.4	107.2	81.2	63.9	49.9	39.7	34.0	29.9	23.9	20.0	10.6
1.80V	270.9	175.4	129.4	102.8	77.0	62.8	48.6	39.3	33.2	29.4	23.6	19.8	10.5
1.85V	225.8	152.6	114.9	91.9	71.6	57.5	43.6	36.1	31.1	26.9	22.2	18.6	9.87