



JM Series lead-acid battery JM12-220(A)


General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Excellent deep cycle discharge capability
- Strong high and low temperature performance
- Precision sealing technology
- Long life



Dimension:520(L)×268(W) ×220(H)×223(TH)/(±3)

Unit: mm



Specification	
Nominal Voltage	12V
Nominal Capacity	220Ah@10hour-rate to 1.80V per cell @25°C
Design life	10 years
Terminal	M8
Approx. Weight	Approx64.0kg±3% (141.1±3%lbs)
Container Material	ABS(UL94-HB, UL94-V0 Optional)
short-circuit current	2926A
Internal resistance(Full charged at 25°C:)	4.1 mΩ
Self discharge	3% of capacity declined per month at 25°C
Operating Temperature	
Discharge:	-20 ~50°C(-4~ 122°F)
Charge :	-20 ~50°C(-4~ 122°F)
Storage:	-20 ~50°C(-4~ 122°F)
Charge Method(25 °C)	
Charge current:	Max. 55A;Recom.22A
Float charge:13.5-13.8V	recom.13.8V(-18mV/ °C)
Equalize charge:13.8-14.1V	recom.14.1V(-24mV/ °C)
Cycle charge:14.4-15.0V	recom.14.7V(-30mV/ °C)

Standards

Executive standard: IEC 60896-21/22,
GB/T 19638.1-2014

Applications

- UPS/EPS
- Power systems
- Telecommunications system
- Emergency lighting、 Auto control system
- Solar/wind generating storage cyclic
- Other general purpose

Rated Capacity

10Hour Rate (22.0A to 10.8V)	220.0Ah
3Hour Rate (58.5A to 10.2V)	175.5Ah
1Hour Rate (139.1A to 9.6V)	139.1Ah

Attain Certificate


			RoHS

Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.




JM Series lead-acid battery JM12-220(A)


Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of temperature on float life



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	385.6	233.7	174.6	139.1	103.3	82.5	62.1	50.0	42.5	36.2	27.9	23.2	12.1
1.65V	370.5	224.4	167.6	133.7	100.3	80.6	60.1	48.4	41.4	35.6	27.6	22.9	11.9
1.70V	347.0	214.4	160.2	128.1	96.3	77.2	58.5	47.3	40.4	34.9	27.2	22.6	11.8
1.75V	322.9	202.9	153.1	124.1	92.3	74.5	56.8	46.1	39.3	34.0	26.8	22.3	11.8
1.80V	304.1	197.4	147.7	118.7	88.0	72.2	56.1	44.8	38.3	33.0	26.3	22.0	11.7
1.85V	252.4	167.0	128.9	104.4	79.5	63.9	49.3	40.6	34.9	30.1	24.7	20.3	11.2

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	677.4	424.5	317.7	254.8	191.3	151.8	117.1	93.6	80.0	69.4	54.5	45.6	23.9
1.65V	657.2	411.8	307.5	247.5	186.5	149.2	115.3	91.4	78.2	68.8	54.0	45.1	23.6
1.70V	624.8	397.5	303.9	241.0	183.8	144.4	110.5	89.3	76.5	67.4	53.3	44.5	23.3
1.75V	589.9	383.9	291.3	235.9	178.7	140.5	109.8	87.3	74.8	65.9	52.6	44.0	23.2
1.80V	557.9	370.6	280.3	226.2	169.5	138.3	106.8	86.4	73.1	64.7	51.9	43.5	23.1
1.85V	464.9	322.4	249.1	202.1	157.4	126.5	95.9	79.4	68.4	59.2	48.8	41.0	21.7