



Electric vehicle long life battery 6-DZFC-22






General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Strong high and low temperature performance
- Low self-discharge rate

Dimension:182(L)×77(W) ×170(H)×170(TH)/(±3)

Unit: mm



Specification

Nominal Voltage	12V
Nominal Capacity	22Ah@2Hour-rate to 1.75V per cell@25℃
Design life	5 years
Terminal	M5
Approx. Weight	Approx. 6.75kg±3% (14.88lbs±3%)
Container Material	ABS
Self discharge	3% of capacity declined per month at 25℃

Rated Capacity

20Hour Rate (1.37A to 10.5V)	27.4Ah
5Hour Rate (4.7A to 10.5V)	23.5Ah
2Hour Rate (11.0A to 10.5V)	22.0Ah

Operating Temperature

Discharge:	-20 ~50℃(-4~ 122°F)
Charge :	-20 ~50℃(-4~ 122°F)
Storage:	-20 ~50℃(-4~ 122°F)

Charge Method(25 °C)

Max charge current	3.30A
Float Use:	13.7-13.9V@25
Cycle Use :	14.7-14.9V,@25

Standards

Executive standard :T/ZJXDC 001-2021

Applications

- Electric vehicle
- Electric wheelchair
- Electric scooter
- Electric play car for children
- Garbage truck
- Patrol car

Attain Certificate




Disclaimer: Manufacturers have the right to self-modify the parameters of the product updates, please keep in touch with manufacturers to obtain the latest information.




Electric vehicle long life battery 6-DZFC-22




Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of discharge depth on cycle life



Constant Current Discharge Characteristics Unit: A (25 ,77)

FV/Time	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	31.5	17.5	11.40	7.88	4.84	2.99	2.52	1.39
1.65V	30.8	17.4	11.30	7.82	4.81	2.96	2.50	1.38
1.70V	30.2	17.3	11.20	7.69	4.76	2.94	2.47	1.38
1.75V	30.0	17.0	11.00	7.60	4.70	2.91	2.45	1.37
1.80V	28.7	16.6	10.80	7.57	4.59	2.91	2.43	1.36
1.85V	26.2	15.4	10.30	7.13	4.36	2.78	2.35	1.34

Constant Power Discharge Characteristics Unit: W/cell (25 ,77)

FV/Time	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	56.9	33.2	21.40	15.00	9.20	5.82	4.85	2.75
1.65V	56.2	32.9	21.30	14.80	9.14	5.77	4.80	2.74
1.70V	56.2	32.6	21.30	14.70	9.08	5.74	4.74	2.73
1.75V	55.9	32.3	21.10	14.60	9.03	5.71	4.72	2.71
1.80V	54.4	32.0	21.10	14.60	8.91	5.66	4.66	2.70
1.85V	49.9	29.7	20.10	13.90	8.51	5.47	4.58	2.67